

STUFFF™ LUBRICANTS



Concrete STUFFF™

Bio-based Concrete Release Agent designed to create a quick, easy and clean release of concrete. It prevents the concrete from bonding to equipment, mixers, precast structures, pipes, curbs, beams, forms and molds.

APPLICATIONS

Use undiluted. Spray, brush or roll on forms, molds, equipment, tools, and other surfaces. Typically, only minimal amounts are required to achieve its intended technical effects.

- Coats metal surfaces and prevents rust
- Lubricates to create easy release of material
- Protects against wear and corrosion
- Keeps equipment clean
- Prevents material buildup
- Restores metals



FEATURES & BENEFITS

- Works for wet & dry applications
- Provides safe and compliant alternative to using diesel
- Will not adversely affect materials
- Displaces water
- Slow evaporation rate
- Free of petroleum, mineral oil, water and solvents
- Requires less product per application
- Reduces fire hazards, high flash point >331°F
- Offers safer and cleaner work environment
- Reduces the negative impacts of spills and leaks
- Negligible odor
- Lowers costs associated with equipment maintenance and replacement, labour, health & safety, storage, disposal and remediation



ENVIRONMENTAL BENEFITS

- Worker friendly
 - Non-toxic, non-carcinogenic
- Environmentally friendly
 - Non-polluting
 - Readily biodegradable
 - Less mist & emissions
 - Safe for environmentally sensitive areas, ideal for applications where there is a risk of oil being lost directly in the environment (aquatic, forestry, agriculture)
- Natural oil-based product formulated from base stock of waste cooking oil
 - Production diverts waste from landfills and waterways
 - Use of renewable resources avoids the upstream pollution associated with petroleum extraction and refining

PHYSICAL DATA

- Appearance: Clear to light yellow liquid
- Odor: Faint odor of fatty substance
- Relative density: 880 kg/m³ (7.34 lbs/gal)
- Evaporation rate: Approx. <1
- Flash point: > 166°C (331°F), Method ASTM D93
- Boiling point: 280°C (536°F)
- Pour point: - 10°C (14°F), product may get cloudy
- Solubility in Water: Insoluble
- Persistence & Degradability: ± 90% within 28 days

Consult SDS for Detailed Information:

- SAFETY & HANDLING - Handle per good industrial hygiene and safety practices.
- FIRST AID - No known hazards when used as directed.
- STORAGE - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- DISPOSAL - Dispose in compliance with federal, provincial, state and local regulations.

DATA PROVIDED IN THIS DOCUMENT IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, STUFFF LUBRICANTS INC. MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, STUFFF LUBRICANTS INC. RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

